

MARMOTECH® NR



CORRUGATED, BLACK,
CONDUCTIVE,
ABRASION RESISTANT
STEEL WIRE HELIX
SYNTHETIC PLYS
TAN NR

TECHNICAL CHARACTERISTICS

Temperature range: -40°C / +70°C (-40°F / +158°F)
Norm: ISO 1307 for dimensional tolerances

Suction and delivery hose suitable for abrasive materials like coal dust, sand, stone chips in dredging operations. Can be assembled with reusable aluminum coupling system.

DESCRIPTION

Tube *

NR, tan, non-conductive, abrasion resistant

Reinforcement

synthetic plies, steel wire helix, on request a/s wires to discharge static electricity

Cover

corrugated, black, conductive, cloth finish. Abrasion, ageing, ozone and oil resistant

Marking

TUDERTECHNICA MARMOTECH® NR

Inside diameter		Outside diameter		Length		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[mt]	[ft]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
51	2,00	76	3,00	40	130	0,9	13	10	150	30	450	2,75	1,85	270	10,63
76	3,00	115	4,53	40	130	0,9	13	10	150	30	450	6,86	4,61	380	14,96
102	4,00	134	5,28	40	130	0,9	13	10	150	30	450	7,48	5,03	550	21,65
127	5,00	163	6,42	40	130	0,9	13	10	150	30	450	9,47	6,36	700	27,56
152	6,00	190	7,48	40	130	0,9	13	10	150	30	450	13,18	8,86	900	35,43
203	8,00	242	9,53	12	39	0,7	10	10	150	30	450	18,6	12,50	1400	55,12
254	10,00	293	11,54	12	39	0,7	10	10	150	30	450	21,17	14,22	1800	70,87
305	12,00	350	13,78	12	39	0,5	7,25	10	150	30	450	28,51	19,16	2400	94,49
357	14,00	410	16,14	12	39	0,5	7,25	10	150	30	450	38,86	26,11	2900	114,17

Data refer to ambient temperature (20°C). Other diameters and pressure only on specific request.
* On request available white NBR tube, black EPDM tube and white food grade compounds tube.

REV-2022-03-23